

# STAL 1032

Optical  
Autolevels



# STAL 1032 - TECHNICAL FEATURES

## Autolevels for immediate use

Accuracy up to 1 mm/Km (double run leveling) makes STAL 1032 an high accuracy autolevel, even for monitoring and engineering works. Horizontal knobs with an unlimited range ensure precise pointing while the circle, graduated in DEG or GON, gives angular measurements. The new redesigned optic is so bright that let you use the new STAL autolevels even in low-light conditions, thanks to the wide objective aperture (40 mm).

STAL 1032, with the same telescope magnifications (thanks to the high accuracy automatic air damping compensator) features higher accuracy, up to 1.0 mm/Km on a double run leveling.

### MODEL STAL 1032

ACCURACY	
Standard deviation per Km (double run leveling)	1.0 mm
TELESCOPE	
Image	Erect
Resolving power	3.98"
Magnification	32x
Objective aperture	40 mm
Field of view	1°20'
Minimum focusing distance	0.75 m
Stadia multiplication constant	100
Stadia addition constant	0
Circular level accuracy	8/2 mm
Hor. circle graduation	1° (DEG model)/1 Gon (GON model)
COMPENSATOR	
Compensator	V Hanging wire/Air damping
Compensator range	±15'
Setting accuracy	±0.3"
Thread	5/8"
PHYSICAL SPECIFICATIONS	
Net Weight	1.45 Kg (with box and accessories 2.5 Kg)
Waterproof/Dustproof	IP54

Illustrations, descriptions and technical specifications are not binding and may change

STONEX AUTHORIZED DEALER

**STONEX®**  
Part of **UniStrong**

Viale dell'Industria 53 - 20037 Paderno Dugnano (MI) - Italy  
Phone +39 02 78619201  
www.stonex.it | info@stonex.it